

BANNER SEAMING HEM TAPE

Our Banner Seaming Hem Tape has great immediate adhesion strength, which results in an amazingly reliable bond. It's perfect for creating joins and hems on PVC banners or doubling the strength of a folded hem. The adhesive strength improves over time, and is perfectly suitable for applications where a high shear resistance is needed. It can be considered a more general-purpose alternative to Bondzilla, more adequate for lighter joining and jobs where tension strength isn't as high. Suitable for virtually all indoor and outdoor applications.

CONSTRUCTION

ADHESIVE	SOLVENT-BASED ACRYLIC
CARRIER	TRANSPARENT PET FILM
LINER	BROWN SILICONE

TECHNICAL SPECIFICATIONS (TYPICAL VALUES)

THICKNESS	0.21MM
ADHESIVE STRENGTH	20N/25MM
INITIAL TACK	18N/25MM
HOLDING POWER	>100 HOURS
APPLICATION TEMPERATURE MIN.	10°C
TEMPERATURE RANGE – SHORT TERM	180°C
TEMPERATURE RANGE – LONG TERM	-40°C TO 100°C

SURFACE PREPARATIONS AND FINISHING

It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry, and free of grease and oil. Expected level of performance will be reached after a bonding period of 24 hours. Always test adhesion prior to application.

STORAGE AND SHELF LIFE

The shelf life of the products is one year when stored at 18-25°C at 30-70% relative humidity and out of direct sunlight, in good packaging.

WARRANTY AND GUARANTEE

Rite Adhesives warrants that its' product complies, within its shelf life, to the specifications mentioned in this Technical Data Sheet.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Eurotech/Rite Adhesives cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tape suitability for their own applications.