

BONDZILLA BANNER BONDING TAPE

Bondzilla has limitless applications, and we recommend it for any and every application where high shear and temperature resistance is required – be it banner bonding, fixing of wall panels, composite panelling, roof, and floor coverings, fixing signs and displays, etc.

CONSTRUCTION

ADHESIVE	RUBBER-BASED
CARRIER	N/A
LINER	SILICONIZED PAPER

TECHNICAL SPECIFICATIONS (TYPICAL VALUES)

THICKNESS	0.4MM
ADHESIVE STRENGTH	45N/25MM
HOLDING POWER	>1500 HOURS
APPLICATION TEMPERATURE MIN.	10°C
TEMPERATURE RANGE – SHORT TERM	N/A
TEMPERATURE RANGE – LONG TERM	-10°C TO 100°C

SURFACE PREPARATIONS AND FINISHING

It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry, and free of grease and oil. Expected level of performance will be reached after a bonding period of 24 hours. Always test adhesion prior to application.

STORAGE AND SHELF LIFE

The shelf life of the products is one year when stored at 18-25°C at 30-70% relative humidity and out of direct sunlight, in good packaging.

WARRANTY AND GUARANTEE

Rite Adhesives warrants that its' product complies, within its shelf life, to the specifications mentioned in this Technical Data Sheet.