

GAFFER TAPE

SINGLE-SIDED CLOTH-BACKING TAPE

SKU #: ET6-6025 AND 6025.20



INTRODUCTION

OUR GAFFER TAPE IS WATERPROOF, LEAVES NO RESIDUE BEHIND AND HAS EXCEPTIONAL TENSILE STRENGTH. IT IS COMMONLY USED TO SECURE CABLES TO A STAGE FLOOR, PODIUM, OR ANOTHER SURFACE, EITHER FOR SAFETY OR CONCEALMENT. IT IS ALSO FREQUENTLY USED FOR ANY IMPROMPTU FIX, SUCH AS TEMPORARILY ATTACHING FIXTURES OR PROPS OR SALVAGING A BROKEN PIECE OF PRODUCTION EQUIPMENT



TECHNICAL DATA

ADHESIVE: NATURAL RUBBER

CARRIER: N/A

LINER: COPOLYMER-COATED CLOTH

TOTAL THICKNESS (MM): 0.300

ADHESIVE STRENGTH: 25N/25MM

TENSILE STRENGTH: 25KG/25MM

HOLDING POWER: >200 HOURS

TEMPERATURE RANGE (LONG TERM) (°C): -10 TO 60

TEMPERATURE RANGE (SHORT TERM) (°C): 80

APPLICATION TEMPERATURE MINIMUM (°C): 10

LENGTH (M): 20/40

WIDTHS (MM): 48

SURFACE PREPARATION

IT IS ESSENTIAL, AS WITH ALL PRESSURE-SENSITIVE TAPES, THAT THE SURFACE TO WHICH THE TAPE IS APPLIED BE CLEAN, DRY, AND FREE OF GREASE AND OIL.

STORAGE AND SHELF LIFE

THE SHELF LIFE OF THE PRODUCTS IS 18 MONTHS WHEN STORED AT 18-25°C AT 30-70% RELATIVE HUMIDITY AND OUT OF DIRECT SUNLIGHT, IN GOOD PACKAGING.

WARRANTY AND GUARANTEE

RITE ADHESIVE WARRANTS THAT ITS PRODUCT COMPLIES, WITHIN ITS SHELF LIFE, TO THE SPECIFICATIONS MENTIONED IN THIS TECHNICAL DATA SHEET.

OTHER INFORMATION

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH, BUT THE USER SHOULD ASSURE HIMSELF THAT THE PERFORMANCE OF THE PRODUCT IS SUFFICIENT FOR HIS APPLICATION. THE QUOTED VALUES ARE AVERAGE AND SHOULD NOT BE TAKEN AS MAXIMUM OR MINIMUM VALUES FOR SPECIFIC PURPOSES. EUROTECH/RITE ADHESIVES CAN NOT BE HELD RESPONSIBLE FOR PRODUCT FAILURE UNLESS FULL TESTING HAS BEEN CARRIED OUT. THE CLIENT HAS TO DECIDE ON THE TAPE SUITABILITY FOR THEIR OWN APPLICATIONS.

