



## INTRODUCTION

IBEX WAS DESIGNED TO ADHERE TO A VARIETY OF SURFACES LIKE PLASTICS, METALS, WOOD, AND GLASS. IT CAN ALSO BE USED FOR NUMEROUS PROJECTS, SUCH AS AUTOMOTIVE, ELECTRICAL, AND WINDOW GLAZING APPLICATIONS, TO SEAL WINDOWS FROM WIND AND MOISTURE, AND SOUND. MOUNTING PHOTOS, BONDING TRIMS AND PROFILES, CABLE CLIPS AND COVERS, AND JUST ABOUT EVERYTHING.



## TECHNICAL DATA

ADHESIVE: SOLVENT-BASED ACRYLIC

CARRIER: POLYETHYLENE FOAM

LINER: FILM

TOTAL THICKNESS (MM): 1.13

ADHESIVE STRENGTH: 20N/25MM

INITIAL TACK: 16N/25MM

HOLDING POWER: >200 HOURS

TEMPERATURE RANGE (LONG TERM) (°C): -30 TO 100

TEMPERATURE RANGE (SHORT TERM) (°C): 120

APPLICATION TEMPERATURE MINIMUM (°C): 10

LENGTH (M): 50

COLOUR: WHITE

## SURFACE PREPARATION

IT IS ESSENTIAL, AS WITH ALL PRESSURE-SENSITIVE TAPES, THAT THE SURFACE TO WHICH THE TAPE IS APPLIED BE CLEAN, DRY, AND FREE OF GREASE AND OIL.

## STORAGE AND SHELF LIFE

THE SHELF LIFE OF THE PRODUCTS IS ONE YEAR WHEN STORED AT 18-25°C AT 30-70% RELATIVE HUMIDITY AND OUT OF DIRECT SUNLIGHT, IN GOOD PACKAGING.

## WARRANTY AND GUARANTEE

RITE ADHESIVE WARRANTS THAT ITS PRODUCT COMPLIES, WITHIN ITS SHELF LIFE, TO THE SPECIFICATIONS MENTIONED IN THIS TECHNICAL DATA SHEET.

## OTHER INFORMATION

