

## EXPRESS TAPE – BANNER REINFORCEMENT TAPE

Express Tape, a premium single-sided banner reinforcement tape, boasts a pure polyacrylic composition renowned for its superior ageing resistance. It excels in long-term durability, showing remarkable resilience against weathering and UV exposure. The adhesive quality of Express Tape is particularly effective on low surface energy materials, including foams, polyethylene, and polypropylene films. It is ideally suited for strengthening PVC print media like PVC sheets and banners, ensuring enhanced durability and performance.

### CONSTRUCTION

ADHESIVE	<b>MODIFIED ACRYLIC DISPERSION</b>
CARRIER	<b>PES/PVA-SCRIM + BYSONYL</b>
LINER	<b>SILICONISED PAPER IN YELLOW</b>

### TECHNICAL SPECIFICATIONS (TYPICAL VALUES)

THICKNESS	<b>0.53MM</b>
ADHESIVE STRENGTH	<b>32.5N/25MM</b>
SERVICE TEMPERATURE RANGE	<b>-40°C TO 155°C</b>

### SURFACE PREPARATIONS AND FINISHING

Application temperature +10°C to +30°C (environment and substrate). Surfaces must be dry, clean and solid. Clean surfaces with an adequate cleaner. The Express Tape is a pressure sensitive adhesive, and as such must be applied with a maximum of pressure in order to achieve maximum results. Expected level of performance will be reached after a bonding period of 24 hours. Always test adhesion prior to application.

### SHELF LIFE

Store between +10°C and +30°C and in shaded conditions. Shelf life is 24 months when stored as recommended in original unopened packaging.

### WARRANTY AND GUARANTEE

Rite Adhesives warrants that its' product complies, within its shelf life, to its specifications.