

AUTOGRADE

MASKING TAPE

SKU #: ET6-6020, 6021, 6022



INTRODUCTION

AUTOGRADE MASKING TAPE LEAVES NO RESIDUE BEHIND. LOWER QUALITY TAPES WILL HAVE A LOWER QUALITY ADHESIVE. THAT MEANS THAT MORE OFTEN THAN NOT, YOU'LL BE LEFT WITH THE ADHESIVE RESIDUE TO CLEAN UP. THE THICKER LINER MAKES IT EASIER TO REMOVE WHEN THE JOB IS FINALLY DONE. OTHER TAPES USUALLY CUT CORNERS TO SAVE ON COST AND YOU MIGHT END UP WITH A BACKING THAT IS THINNER THAN IT SHOULD BE.



TECHNICAL DATA

ADHESIVE: RUBBER-BASED

LINER: YELLOW CREPE PAPER

TOTAL THICKNESS (MM): 0.120

ADHESIVE STRENGTH: 8N/25MM

INITIAL TACK: N/A

HOLDING POWER: >2 HOURS

TEMPERATURE RANGE (LONG TERM) (°C): -40 TO 100

TEMPERATURE RANGE (SHORT TERM) (°C): 120

APPLICATION TEMPERATURE MINIMUM (°C): N/A

LENGTH (M): 50

SURFACE PREPARATION

IT IS ESSENTIAL, AS WITH ALL PRESSURE-SENSITIVE TAPES, THAT THE SURFACE TO WHICH THE TAPE IS APPLIED BE CLEAN, DRY, AND FREE OF GREASE AND OIL.

STORAGE AND SHELF LIFE

THE SHELF LIFE OF THE PRODUCTS IS ONE YEAR WHEN STORED AT 18-25°C AT 30-70% RELATIVE HUMIDITY AND OUT OF DIRECT SUNLIGHT, IN GOOD PACKAGING.

WARRANTY AND GUARANTEE

RITE ADHESIVE WARRANTS THAT ITS PRODUCT COMPLIES, WITHIN ITS SHELF LIFE, TO THE SPECIFICATIONS MENTIONED IN THIS TECHNICAL DATA SHEET.

OTHER INFORMATION

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH, BUT THE USER SHOULD ASSURE HIMSELF THAT THE PERFORMANCE OF THE PRODUCT IS SUFFICIENT FOR HIS APPLICATION. THE QUOTED VALUES ARE AVERAGE AND SHOULD NOT BE TAKEN AS MAXIMUM OR MINIMUM VALUES FOR SPECIFIC PURPOSES. EUROTECH/RITE ADHESIVES CAN NOT BE HELD RESPONSIBLE FOR PRODUCT FAILURE UNLESS FULL TESTING HAS BEEN CARRIED OUT. THE CLIENT HAS TO DECIDE ON THE TAPE SUITABILITY FOR THEIR OWN APPLICATIONS.

