

BLAZEBOND

HEAT RESISTANT TISSUE TAPE

SKU #: ET6-6090, ET6-6091 AND ET6-6092

INTRODUCTION

BLAZEBOND IS AN EXTREMELY HEAT-RESISTANT, HIGH BOND, AND EASY-TO-USE TISSUE TAPE. IT REPLACES THE USE OF HYENA TISSUE TAPE, BY ALLOWING ITS USE IN HEAT-INDUCING ENVIRONMENTS AND MACHINERY, DUE TO ITS 200°C TEMPERATURE RESISTANCE.



TECHNICAL DATA

ADHESIVE: SOLVENT-BASED ACRYLIC

CARRIER: TISSUE

LINER: PE PAPER

TOTAL THICKNESS (MM): 0.170

ADHESIVE STRENGTH: 15N/25MM

INITIAL TACK: 15N/25MM

TEMPERATURE RANGE (LONG TERM) (°C): -20 TO 120

TEMPERATURE RANGE (SHORT TERM) (°C): -40 TO 200

APPLICATION TEMPERATURE MINIMUM (°C): -10

WIDTH(S) (MM): 12, 24, 300

LENGTH (M): 50

COLOUR: TRANSPARENT

SURFACE PREPARATION

IT IS ESSENTIAL, AS WITH ALL PRESSURE-SENSITIVE TAPES, THAT THE SURFACE TO WHICH THE TAPE IS APPLIED BE CLEAN, DRY, AND FREE OF GREASE AND OIL.

STORAGE AND SHELF LIFE

THE SHELF LIFE OF THE PRODUCTS IS ONE YEAR WHEN STORED AT 18-25°C AT 30-70% RELATIVE HUMIDITY AND OUT OF DIRECT SUNLIGHT, IN GOOD PACKAGING.

WARRANTY AND GUARANTEE

RITE ADHESIVES WARRANTS THAT ITS PRODUCT COMPLIES, WITHIN ITS SHELF LIFE, TO THE SPECIFICATIONS MENTIONED IN THIS TECHNICAL DATA SHEET.

OTHER INFORMATION