



INTRODUCTION

BONDZILLA HAS LIMITLESS APPLICATIONS, AND WE RECOMMEND IT FOR ANY AND EVERY APPLICATION WHERE HIGH SHEAR AND TEMPERATURE RESISTANCE IS REQUIRED – BE IT BANNER BONDING, FIXING OF WALL PANELS, COMPOSITE PANELING, ROOF, AND FLOOR COVERINGS, FIXING SIGNS AND DISPLAYS, ETC.



TECHNICAL DATA

ADHESIVE: RUBBER-BASED

CARRIER: N/A

LINER: SILICONIZED PAPER

TOTAL THICKNESS (MM): 0.400

ADHESIVE STRENGTH: 45N/25MM

INITIAL TACK: N/A

HOLDING POWER: >1500 HOURS

TEMPERATURE RANGE (LONG TERM) (°C): -10 TO 100

TEMPERATURE RANGE (SHORT TERM) (°C): N/A

APPLICATION TEMPERATURE MINIMUM (°C): 10

LENGTH (M): 50

COLOUR: TRANSPARENT

SURFACE PREPARATION

IT IS ESSENTIAL, AS WITH ALL PRESSURE-SENSITIVE TAPES, THAT THE SURFACE TO WHICH THE TAPE IS APPLIED BE CLEAN, DRY, AND FREE OF GREASE AND OIL.

STORAGE AND SHELF LIFE

THE SHELF LIFE OF THE PRODUCTS IS ONE YEAR WHEN STORED AT 18-25°C AT 30-70% RELATIVE HUMIDITY AND OUT OF DIRECT SUNLIGHT, IN GOOD PACKAGING.

WARRANTY AND GUARANTEE

RITE ADHESIVE WARRANTS THAT ITS PRODUCT COMPLIES, WITHIN ITS SHELF LIFE, TO THE SPECIFICATIONS MENTIONED IN THIS TECHNICAL DATA SHEET.

OTHER INFORMATION

