

HIGH BOND

POLYESTER TAPE

SKU #: ET6-6030E, 6032E



INTRODUCTION

OUR PE HIGH BOND TAPE OFFERS AN EXCELLENT IMMEDIATE ADHESION PERFORMANCE AND SECURE RELIABLE BONDING STRENGTH, LAMINATION TO BORDER OR PROFILES. USED FOR MANY PERMANENT EDGING AND REINFORCING TYPES OF APPLICATIONS, PRINTING PLATE, REGISTRATION HOLE REINFORCEMENT, APPLICATIONS REQUIRING PUNCTURE RESISTANCE.



TECHNICAL DATA

ADHESIVE: SOLVENT-BASED ACRYLIC

CARRIER: TRANSPARENT PET FILM

LINER: RED MOPP FILM

TOTAL THICKNESS (MM): 0.210

ADHESIVE STRENGTH: 20N/25MM

INITIAL TACK: 18N/25MM

HOLDING POWER: >100 HOURS

TEMPERATURE RANGE (LONG TERM) (°C): -40 TO 100

TEMPERATURE RANGE (SHORT TERM) (°C): 180

APPLICATION TEMPERATURE MINIMUM (°C): 10

LENGTH (M): 50

COLOUR: TRANSPARENT

SURFACE PREPARATION

IT IS ESSENTIAL, AS WITH ALL PRESSURE-SENSITIVE TAPES, THAT THE SURFACE TO WHICH THE TAPE IS APPLIED BE CLEAN, DRY, AND FREE OF GREASE AND OIL.

STORAGE AND SHELF LIFE

THE SHELF LIFE OF THE PRODUCTS IS ONE YEAR WHEN STORED AT 18-25°C AT 30-70% RELATIVE HUMIDITY AND OUT OF DIRECT SUNLIGHT, IN GOOD PACKAGING.

WARRANTY AND GUARANTEE

RITE ADHESIVE WARRANTS THAT ITS PRODUCT COMPLIES, WITHIN ITS SHELF LIFE, TO THE SPECIFICATIONS MENTIONED IN THIS TECHNICAL DATA SHEET.

OTHER INFORMATION

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH, BUT THE USER SHOULD ASSURE HIMSELF THAT THE PERFORMANCE OF THE PRODUCT IS SUFFICIENT FOR HIS APPLICATION. THE QUOTED VALUES ARE AVERAGE AND SHOULD NOT BE TAKEN AS MAXIMUM OR MINIMUM VALUES FOR SPECIFIC PURPOSES. EUROTECH/RITE ADHESIVES CAN NOT BE HELD RESPONSIBLE FOR PRODUCT FAILURE UNLESS FULL TESTING HAS BEEN CARRIED OUT. THE CLIENT HAS TO DECIDE ON THE TAPE SUITABILITY FOR THEIR OWN APPLICATIONS.

