

UHB CLEAR

ACRYLIC FOAM TAPE, CLEAR

SKU #: ET6-6056E, 6057E



INTRODUCTION

OUR ACRYLIC FOAM TAPE IS DESIGNED TO PROVIDE VERY HIGH BOND STRENGTH ON A VARIETY OF SUBSTRATES, AS WELL AS TO BE USED TO REPLACE MECHANICAL FASTENERS IN THE APPLIANCE, AUTOMATIVE, SIGN AND GRAPHIC INDUSTRIES. ASSEMBLY OF SIGNS AND DISPLAYS, MOUNTING OF TRIMS, FIXINGS, BADGES AND VEHICLE PANELS AND ACCESSORIES.



TECHNICAL DATA

ADHESIVE: SOLVENT-BASED ACRYLIC

CARRIER: ACRYLIC FOAM

LINER: PE FILM

TOTAL THICKNESS (MM): 1.0

ADHESIVE STRENGTH: 50N/25MM

INITIAL TACK: N/A

HOLDING POWER: >1500 HOURS

TEMPERATURE RANGE (LONG TERM) (°C): -10 TO 120

TEMPERATURE RANGE (SHORT TERM) (°C): 160

APPLICATION TEMPERATURE MINIMUM (°C): 10

LENGTH (M): 33

COLOUR: TRANSPARENT

SURFACE PREPARATION

IT IS ESSENTIAL, AS WITH ALL PRESSURE-SENSITIVE TAPES, THAT THE SURFACE TO WHICH THE TAPE IS APPLIED BE CLEAN, DRY, AND FREE OF GREASE AND OIL.

STORAGE AND SHELF LIFE

THE SHELF LIFE OF THE PRODUCTS IS ONE YEAR WHEN STORED AT 18-25°C AT 30-70% RELATIVE HUMIDITY AND OUT OF DIRECT SUNLIGHT, IN GOOD PACKAGING.

WARRANTY AND GUARANTEE

RITE ADHESIVE WARRANTS THAT ITS PRODUCT COMPLIES, WITHIN ITS SHELF LIFE, TO THE SPECIFICATIONS MENTIONED IN THIS TECHNICAL DATA SHEET.

OTHER INFORMATION

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH, BUT THE USER SHOULD ASSURE HIMSELF THAT THE PERFORMANCE OF THE PRODUCT IS SUFFICIENT FOR HIS APPLICATION. THE QUOTED VALUES ARE AVERAGE AND SHOULD NOT BE TAKEN AS MAXIMUM OR MINIMUM VALUES FOR SPECIFIC PURPOSES. EUROTECH/RITE ADHESIVES CAN NOT BE HELD RESPONSIBLE FOR PRODUCT FAILURE UNLESS FULL TESTING HAS BEEN CARRIED OUT. THE CLIENT HAS TO DECIDE ON THE TAPE SUITABILITY FOR THEIR OWN APPLICATIONS.

